

TEW Wire

For use in internal wiring of electrical and electronic equipment. Applications include electric ranges, heating equipment, lighting fixtures, panels and meters. CSA & UL Approved. For applications up to 600 Volts. Copper conductors are stranded with PVC Insulation. Temperature Rating: -40°C to 105°C (-40°F to 221°F). Available with bare copper or tin-plated copper conductors.



B



TEW Wire – Bare Copper Conductors: 30m (98.4') Spools

***NEW**
***NEW**

| GA | O.D. | Stranding | Black | Blue | Brown | Green | Grey | Orange | Purple | Red | White | Yellow |
|----|-------|-------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| 18 | .109" | 16 x .010" | 768600 | 768601 | 768602 | 768603 | 768608 | 768604 | 768599 | 768605 | 768606 | 768607 |
| 16 | .122" | 26 x .010" | 768609 | 768610 | 768611 | 768612 | 768617 | 768613 | 768598 | 768614 | 768615 | 768616 |
| 14 | .136" | 41 x .010" | 768618 | 768619 | 768620 | 768621 | 768626 | 768622 | 768597 | 768623 | 768624 | 768625 |
| 12 | .159" | 65 x .010" | 768627 | 768628 | 768629 | 768630 | *768635 | 768631 | *768596 | 768632 | 768633 | 768634 |
| 10 | .183" | 105 x .010" | *768636 | *768637 | *768638 | *768639 | | *768640 | | *768641 | *768642 | *768643 |

O.D. = Outside Diameter

***NEW**

TEW Wire – Bare Copper Conductors: 300m (984') Spools

| GA | O.D. | Stranding | Black | Blue | Brown | Green | Grey | Orange | Purple | Red | White | Yellow |
|----|-------|-------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| 18 | .109" | 16 x .010" | *768600M | *768601M | *768602M | *768603M | *768608M | *768604M | *768599M | *768605M | *768606M | *768607M |
| 16 | .122" | 26 x .010" | *768609M | *768610M | *768611M | *768612M | *768617M | *768613M | *768598M | *768614M | *768615M | *768616M |
| 14 | .136" | 41 x .010" | *768618M | *768619M | *768620M | *768621M | *768626M | *768622M | *768597M | *768623M | *768624M | *768625M |
| 12 | .159" | 65 x .010" | *768627M | *768628M | *768629M | *768630M | *768635M | *768631M | *768596M | *768632M | *768633M | *768634M |
| 10 | .183" | 105 x .010" | *768636M | *768637M | *768638M | *768639M | | *768640M | | *768641M | *768642M | *768643M |

O.D. = Outside Diameter



Tinned for Marine Applications!

TEW Wire – Tinned Copper Conductors: 30m (98.4') Spools

| GA | O.D. | Stranding | Black | Blue | Brown | Green | Grey | Orange | Purple | Red | White | Yellow |
|----|-------|-------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 18 | .109" | 16 x .010" | 768654 | 768655 | 768656 | 768657 | 768663 | 768658 | 768662 | 768659 | 768660 | 768661 |
| 16 | .122" | 26 x .010" | 768664 | 768665 | 768666 | 768667 | 768673 | 768668 | 768672 | 768669 | 768670 | 768671 |
| 14 | .136" | 41 x .010" | 768674 | 768675 | 768676 | 768677 | 768683 | 768678 | 768682 | 768679 | 768680 | 768681 |
| 12 | .159" | 65 x .010" | 768684 | 768685 | 768686 | 768687 | 768693 | 768688 | 768692 | 768689 | 768690 | 768691 |
| 10 | .183" | 105 x .010" | 768694 | 768695 | 768696 | 768697 | 768703 | 768698 | 768702 | 768699 | 768700 | 768701 |

O.D. = Outside Diameter

***NEW**

TEW Wire – Tinned Copper Conductors: 300m (984') Spools

| GA | O.D. | Stranding | Black | Blue | Brown | Green | Grey | Orange | Purple | Red | White | Yellow |
|----|-------|-------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| 18 | .109" | 16 x .010" | *768654M | *768655M | *768656M | *768657M | *768663M | *768658M | *768662M | *768659M | *768660M | *768661M |
| 16 | .122" | 26 x .010" | *768664M | *768665M | *768666M | *768667M | *768673M | *768668M | *768672M | *768669M | *768670M | *768671M |
| 14 | .136" | 41 x .010" | *768674M | *768675M | *768676M | *768677M | *768683M | *768678M | *768682M | *768679M | *768680M | *768681M |
| 12 | .159" | 65 x .010" | *768684M | *768685M | *768686M | *768687M | *768693M | *768688M | *768692M | *768689M | *768690M | *768691M |
| 10 | .183" | 105 x .010" | *768694M | *768695M | *768696M | *768697M | *768703M | *768698M | *768702M | *768699M | *768700M | *768701M |

O.D. = Outside Diameter