

Luminaire Disconnect

The Marrette® Luminaire Disconnect protects electricians servicing fluorescent lights over 150 V from electrical shock!

Suited for

- Fluorescent lighting fixture and ballast (OEMs)
- Electricians servicing fluorescent light fixtures
- Maintenance personnel requiring an electrical disconnect

Specifications

Housing:	Polycarbonate
Contacts:	Tin-plated brass
Integral leads:	Insulated 18 AWG solid copper
Max. temp. rating:	105°C
Flammability:	UL94-V2 (V0 available on request)
Electrical rating:	4 A, 600 V
Standards:	CSA Certified, UL listed, NEC 410.73(G) 2005 edition compliant



Luminaire Disconnect

Ordering Information

Model	Description
LD2C-D	2-pole luminaire disconnect (marrettes not included)
LD3C-D	3-pole luminaire disconnect (marrettes not included)
LD2-C	2-pole luminaire disconnect (2 x 4 marrettes 333 /inner bag)
LD3-C	3-pole luminaire disconnect (6 of each marrettes (331 + 333) /inner bag)



	Cat. No.	Packaging Format	Std. Pkg. (Min./Mult.)		
BULK	LD2C-D	Box	Sold without marrettes Sold in multiple of 500	Inner: Outer: Master:	50 per inner bag 250 per outer box 500 in master box
	LD3C-D	Box			
KITS	LD2-C	Bag	Sold with marrettes Sold in multiple of 20	Inner: Outer: Master:	2 per inner bag 20 per outer bag 200 in master box
	LD3-C	Bag			