




W5325-TOW



UPC Code : 078477937785

Country Of Origin : United States

RoHS Compliant : Yes



15 Amp Decora Weather & Tamper-Resistant Duplex Outlet

15 Amp, 125 Volt, NEMA: 5-15R, Pole: 2, 3-Wire, Weather and Tamper-Resistant, Decora, Duplex Receptacle/Outlet, Straight Blade, Grounding, Quickwire Push-In & Side, Standards and Certifications: UL/CSA, Warranty: 2 Year Limited, NEC compliant – White

- WEATHER-RESISTANT – UV stabilized thermoplastic construction and extra corrosion protection to withstand the rigors of exposure to the elements
- SAFE – Tamper-Resistant shutters protects from foreign objects being inserted into receptacle to ensure personal safety
- EASY – Quickwire push-in and side wiring for easy installation
- OUTDOOR USE – Must be installed in proper weatherproof enclosure with approved caulk and gaskets

Technical Information

Product Features

Amperage : 15 A

Color : White

Device Type : Decora Receptacle

Feature : Weather and Tamper-Resistant

Type : Decora Duplex Receptacle

Weather Resistant : Yes

Wire : 3

Electrical Specifications

Amperage : 15 A

Grounding : Grounding

Pole : 2

Wire : 3

Mechanical Specifications

Termination : Quickwire Push-In & Side

Torque Range : 14 - 18 in.-lbs

Standards and Certifications

CSA : C22.2 No. 42: File 152105; Class 6233-01

NEMA : 5-15R

NOM : NOM Certified

UL 498 : File E13399

Warranty

Warranty : 2-Year Limited

Features and Benefits

- UV stabilized thermoplastic construction and extra corrosion protection to withstand exposure to the elements
- QuickWire™ push-in and side wiring for easy installation
- Terminal screws accept up to #12 AWG copper or copper-clad wire
- QuickWire push-in terminals accept #14 AWG solid copper wire only
- Shallow depth for maximum wiring room
- Heavy-gauge zinc-plated steel mounting strap
- Additional material added to strap to help reinforce and prevent excessive bending of the break-off tabs
- Shutter mechanism inside the receptacle blocks access to the contacts unless a two-prong plug is inserted, helping ensure hairpins, keys, etc., will be locked out
- WR symbol on front of device and TR symbol on strap make it easy to identify and assures they meet the latest NEC requirements

- Ultrasonic welding, heavy-duty construction offers long, trouble-free service life
- Limited 2-year warranty
- Ideal solution for both outdoor residential and commercial areas, including patios, decks and near pools and hot tubs
- For outdoor use with Leviton's code compliant weatherproof covers
- **CAUTION:** To clean use a damp cloth with mild soap. DO NOT use disinfecting products, including foggers, sprays, or other types of atomized cleaning agents

SPECIFICATION SUBMITTAL

| | | | |
|----------------------|----------------------|----------------------|----------------------|
| JOB NAME: | CATALOG NUMBERS: | | |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| JOB NUMBER: | <input type="text"/> | <input type="text"/> | <input type="text"/> |

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx



Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/