

TYPE Thin Wall

Features

- 2:1 shrink ratio
- UL Recognized and CSA Certified
- Rated for 600 volts
- Convenient disk dispenser

Benefits

- Provides a wide range of coverage when used on connectors and cable
- Assures product reliability for insulating and protecting terminations and splices
- Ensures reliability
- Protects tubing from damage and keeps it clean



| Catalog Number | Wire Range | Exp. Id. | Rec. Id. | Recovered Wall Thickness | L |
|----------------|------------|----------|----------|--------------------------|----------|
| 24001-B10 | 26-34 | 0.046 | 0.023 | 0.016 | 6" |
| 24002-B10 | 24-30 | 0.063 | 0.031 | 0.017 | 6" |
| 24003-B10 | 22-28 | 0.093 | 0.046 | 0.020 | 6" |
| 24004-B10 | 20-26 | 0.125 | 0.062 | 0.020 | 6" |
| 24005-B10 | 18-22 | 0.187 | 0.093 | 0.020 | 6" |
| 24006-B10 | 14-16 | 0.250 | 0.125 | 0.025 | 6" |
| 24007-B5 | 10-12 | 0.312 | 0.156 | 0.025 | 6" |
| 24008-B5 | 6-8 | 0.375 | 0.187 | 0.025 | 6" |
| 24009-B5 | 4-6 | 0.500 | 0.250 | 0.025 | 6" |
| 24010-B5 | 2/0-2 | 0.750 | 0.375 | 0.030 | 6" |
| 24011-B5 | 4/0-1 | 1.000 | 0.500 | 0.035 | 6" |
| 24999-B12+ | - | - | - | - | - |
| 25001 | 26-34 | 0.046 | 0.023 | 0.016 | 96" Disk |
| 25002 | 24-30 | 0.063 | 0.031 | 0.017 | 96" Disk |
| 25003 | 22-28 | 0.093 | 0.046 | 0.020 | 96" Disk |
| 25004 | 20-26 | 0.125 | 0.062 | 0.020 | 96" Disk |
| 25005 | 18-22 | 0.187 | 0.093 | 0.020 | 96" Disk |
| 25006 | 14-16 | 0.250 | 0.125 | 0.025 | 96" Disk |
| 25007 | 10-12 | 0.3112 | 0.156 | 0.025 | 96" Disk |
| 25008 | 6-8 | 0.375 | 0.187 | 0.025 | 96" Disk |
| 25009 | 4-6 | 0.500 | 0.250 | 0.025 | 96" Disk |
| 25010 | 2/0-2 | 0.750 | 0.375 | 0.030 | 96" Disk |
| 25011 | 4/0-1 | 1.000 | 0.500 | 0.035 | 96" Disk |

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
+ 24999-B12 contains 3 ea. 24005, 24006, 24008, 24009
UL File E158587

TYPE Thin Wall

Features

- 2:1 shrink ratio
- UL Recognized and CSA Certified
- Rated for 600 volts

Benefits

- Provides a wide range of coverage when used on connectors and cable
- Assures product reliability for insulating and protecting terminations and splices
- Ensures reliability



| Catalog Number | Wire Range | Exp. Id. | Rec. Id. | Recovered Wall Thickness | Cut Length |
|----------------|------------|----------|----------|--------------------------|------------|
| 26001 | 26-34 | 0.046 | 0.023 | 0.016 | 1000' |
| 26002 | 24-30 | 0.063 | 0.031 | 0.017 | 1000' |
| 26003 | 22-28 | 0.093 | 0.046 | 0.020 | 500' |
| 26004 | 20-26 | 0.125 | 0.062 | 0.020 | 500' |
| 26005 | 18-22 | 0.187 | 0.093 | 0.020 | 200' |
| 26006 | 14-16 | 0.250 | 0.125 | 0.025 | 200' |
| 26007 | 10-12 | 0.312 | 0.156 | 0.025 | 500' |
| 26008 | 6-8 | 0.375 | 0.187 | 0.025 | 200' |
| 26009 | 4-6 | 0.500 | 0.250 | 0.025 | 200' |
| 26010 | 2/0-2 | 0.750 | 0.375 | 0.030 | 200' |
| 26011 | 4/0-1 | 1.000 | 0.500 | 0.035 | 200' |

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)