



SKU: RLT-7

UPC: 0783669715743

Features & Benefits:

Description: Permagraund Copper Grounding Connector, Main Conductor Range 250-4/0, Tap Range 250-4/0, Ground Rod Size 3/4in, Rebar Sizes #5-#6, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Catalog Number	ILD-998
ILSCOs Die Index Number	1011

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 4/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	250 kcmil - 4/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	3/4
Rebar Size(s) Main	#5 (5/8)

Dimensions

Height (IN)	2.191
Height BX (IN)	4.75
Height (mm)	55.6514
Length (IN)	1.344
Length (mm)	34.1376
Weight (LB)	0.42
Weight BX (LB)	8.6618
Width (IN)	0.875
Width BX (IN)	7
Width (mm)	22.225

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type Stranded

General

Bag Quantity 1
Carton Quantity Description STD PACK QTY 20
Direct Burial Yes
Dual Rated No
NEMA Code S-573-3
UPC Code 78366971574

Bolt and Screw Sizes

Mounting Bolt/Stud Size NA

Testing Standards

CSA File Number LR-5465
CSA Standard C22.2 No. 41
Prop65 Compliance This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number 667P
UL / CULUS Specification UL 467 Listed
UL File Number E34440

Environment and Temperature

Temperature Rating NA

Color

Color Copper