Production Specifications

Eaton S811+R13P3S

Catalog number: S811+R13P3S

Eaton S811+ soft starter, Soft Starter ,110 mm, 135 A, Pimp control with OPT Inside delta



General specifications

Product Name	**Catalog Number**
Eaton S811+ soft starter	S811+R13P3S
UPC	**Product Length/Depth**
786685558967	13 in
Product Height	**Product Width**
10 in	9.5 in
Product Weight	**Certifications**
12.5 lb	Contact Manufacturer

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Frame size

R

Special features

30 second ramp or 450% current limit at 50°C, inside-the-delta connection, pump control and extended ramp functions

Type

Premium

Rating

30 kW at 230 V, 55 kW at 380-400 V, 59 kW at 440 V

Amperage Rating

42-135A

Resources

Application notes

S8x1 adjustment - Switching from S801+ to S811+

Brochures

S811+/S801+ soft starters

Catalogs

Eaton's Volume 2—Commercial Distribution

Product Datasheet - S811+R13P3S

Product Range Catalog Drives Engineering

Drawings

Type S811+ Soft Starter - N-frame

Installation instructions

Instructions for S811+ Soft Starter, S811+N... and S811+R

Multimedia

Soft Starter Product Family Overview

Soft starter DS7 up to 200 A

Soft Starter DS7 up to 32 A

Specifications and datasheets

Eaton Specification Sheet - S811+R13P3S

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia