Production Specifications

Eaton RS2-11-C3



Catalog number: RS2-11-C3

Eaton RS2 Series Safety Interlock Switch, Magnetic Reed Switch, Polyamide enclosure, 300 mA max DC, 1 Normally Open and 1 Normally Closed, 300 mA at 24 Vdc, 10 Ft. (3m) Cable, < 10% accuracy, 10 Ft. (3m)

General specifications

Product Name
Eaton RS-Titan non-contact door interlock safety switch

Catalog Number
RS2-11-C3

UPC
786685884721

Product Length/Depth
.94 in

Product Height
2 in

Product Width
.44 in

Product Weight
.3625 lb

Warranty
1 year

Compliances
CE Marked

Certifications
UL Listed

Catalog Notes
0

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Contact configuration

1 NO-1 NC

Switch type

Magnetic reed switch

Cord length

120 ft

Operating temperature - min

14 °F

Maximum DC current

300 mA

Connection

10 ft (3 m) cable

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Polyamide

Type

LIMIT SWITCHES

Accuracy

< 10%

Contact Rating

300 mA at 24 Vdc

Operating temperature - max

131 °F

Environmental rating

IP67, IP69K

Resources

Catalogs

Eaton's Volume 8—Sensing Solutions

Specifications and datasheets

Eaton Specification Sheet - RS2-11-C3

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia