

Eaton CHSPT2SURGE

Catalog number: CHSPT2SURGE

Eaton SPD Type 2 CHSP Service Entrance Surge Protection, 120/240V line, 150V L-N, 300V L-L MCOV, 700V L-N, 1200V L-L, 900V N-G, 700V L-G VPR, 22 kA SCCR, NEMA 4, Single-phase, 60 Hz, 5 kA nominal current discharge, 36 kA surge current

General specifications



Product Name

Eaton CHSPT2 surge protection device

Catalog Number

CHSPT2SURGE

UPC

786685971285

Product Length/Depth

7.5 in

Product Height

2 in

Product Width

5 in

Product Weight

.9 lb

Warranty

Limited lifetime

Certifications

UL Recognized cUL Certified UL 1449

Catalog Notes

5kA nominal discharge current. Has 36kA one time surge current rating.

Physical Attributes

Enclosure

NEMA 4

Type

Surge protection device

Performance Ratings

Interrupt rating

200 kAIC

Operating temperature

-40 to 50 °C

Operating voltage

150V L-N, 300V L-L

Phase

Single-phase

Protection

700V L-N, 1200V L-L, 900V N-G, 700V L-G

Surge current

36 kA

Voltage rating

120/240 V

Miscellaneous

Special features

Meets or exceeds the requirements specified in IBC ©2006, CBC2007, and UBC@Zone 4

Resources

Brochures

Product Family Guide

Ultra, Publication No. SA00414002E / VCG1503

Complete Home Protection, Publication No. FL010001EN / 3PC

Eaton Solutions, Publication No. SA00404006E / VCG1302

Storm season is coming. Are you prepared?

Install sheets, CHSPT2

Complete Home Protection, Publication No. BR00414002E / VCG1502

Catalogs

Surge Protection

Specifications and datasheets

Eaton Specification Sheet - CHSPT2SURGE

Warranty guides

Surge Protection Warranty WA00414003E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)