

Eaton XTRE10B22B

Catalog number: XTRE10B22B

XT IEC Control Relay, Screw terminals, 45 mm - standard Frame size, 2NO-2NC contact configuration, 220V 50 Hz, 240V 60 Hz coil, 10A conventional thermal rating, 6A at 220/230/240V; 4A at 380/400/415V rated operational voltage

General specifications



Product Name

Eaton XT IEC control relay

EAN

4015082763985

Product Height

2 in

Product Weight

.3 lb

Catalog Number

XTRE10B22B

Product Length/Depth

3 in

Product Width

3 in

Certifications

UL Listed

defaultTaxonomyAttributeLabel

Frame size

45 mm - standard

Contact configuration

2 NO, 2 NC

Type

Control relay

Terminals

Screw terminals

Rated operational current

4 A at 380/400/415 V

6 A at 220/230/240 V

Conventional thermal current

10A

Coil

220-240 Vac, 50/60 Hz

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTRE 3D Inventor](#)

[XTRE 2D Drawing Xchange](#)

[XTRE AutoCAD 2D Footprint \(mm\)](#)

[XTRE 3D Model Xchange](#)

[XTRE 2D PDF](#)

[XTRE AutoCAD 2D Footprint](#)

Specifications and datasheets

[Eaton Specification Sheet - XTRE10B22B](#)

[Global Data Sheet - XTRE10B22B](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)