

Eaton XTOMP60AC1

Catalog number: XTOMP60AC1

Eaton XT IEC control relay, XT IEC Miniature Overload Relay, 0.4-0.6A overload range, 45 mm - mini Frame size, 1NO-1NC contact configuration, Direct mounting, 10A trip type



General specifications

Product Name

Eaton XT IEC control relay

Catalog Number

XTOMP60AC1

EAN

4015080143338

Product Length/Depth

2 in

Product Height

2.5 in

Product Width

3 in

Product Weight

.2 lb

Compliances

ATEX Compliant CE Marked RoHS Compliant

Certifications

UL Listed CSA Certified IEC 60947 EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Clearance of at least 5 mm is required between the overload relays when fitted directly to contactor.

defaultTaxonomyAttributeLabel

Frame size

45 mm - mini

Contact configuration

1 NO, 1 NC

Overload range

0.4-0.6A

Type

Control relay

Mounting method

Direct

Trip type

10 A

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOM 3D Model Xchange](#)

[XTOM 2D PDF](#)

[XTOM 3D Inventor](#)

[XTOM AutoCAD 2D Footprint](#)

[XTOM AutoCAD 2D Footprint \(mm\)](#)

[XTOM 2D Drawing Xchange](#)

Specifications and datasheets

[Global Data Sheet - XTOMP60AC1](#)

[Eaton Specification Sheet - XTOMP60AC1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)