

Energy Saving PAR



MOL: 3 1/8 in. (79 mm)
Ø 2 1/2 in. (63 mm)

PAR20



MOL: 3 27/32 in. (90 mm)
Ø 3 3/4 in. (95 mm)

PAR30



MOL: 4 11/16 in. (119 mm)
Ø 3 3/4 in. (95 mm)

PAR30LN



MOL: 5 5/16 in. (132 mm)
Ø 4 15/16 in. (80 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Finish	Operating position	Beam angle (°)	Beam spread	CBCP (cd)	Incan. equiv. (W)	Case qty (master)
PAR20													
63797	H35/PAR20/ECO/NFL/120V/STD	35	E26	120	500	2 000	Aluminum	Universal	25	Narrow Flood	850	50	15
PAR30													
63798	H35/PAR30/ECO/FL/120V/STD	35	E26	120	500	2 000	Silver	Universal	30	Flood	900	50	15
63799 [†]	H60/PAR30/ECO/FL/120V/STD	60	E26	120	1 070	1 500	Silver	Universal	30	Flood	1 100	75	15
PAR30LN													
63800	H35/PAR30LN/ECO/FL/120V/STD	35	E26	120	500	2 000	Silver	Universal	30	Flood	900	50	15
PAR38													
63802 [†]	H60/PAR38/ECO/FL/120V/STD	60	E26	120	1 070	1 500	Silver	Universal	30	Flood	1 100	75	15
63803 [†]	H70/PAR38/ECO/FL/120V/STD	70	E26	120	1 301	1 500	Silver	Universal	30	Flood	2 000	90	15



[†] This product is no longer available in Ontario as per Energy Efficiency Regulations.



instant on dimmable



dry
location



UV
stop





ACCUBEAM

ACCUBEAM lamps use a reflector design that forms the light beam before it reaches the lens. The corrugated reflector allows for greater light concentration at the center of the beam providing a light output that is comparable to conventional halogens, while using less wattage. ACCUBEAM was designed to deliver a smooth, precise beam pattern and allows for even light distribution; without hot spots or striations.



PAR30

MOL : 3 5/8 in. (92 mm)
Ø 3 3/4 in. (95 mm)



PAR38

MOL : 5 5/16 in. (135 mm)
Ø 4 3/4 in. (121 mm)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Beam angle (°)	Beam spread	Case qty (master)
PAR30									
50015 ¹	H75PAR30/NSP/5M/130V/STD ACC	75	E26	130	825	5 000	10	Narrow Spot	15
PAR38									
50066 ¹	H45PAR38/SP/5M/130V/STD ACC	45	E26	130	390	5 000	10	Spot	15
50041 ¹	H45PAR38/FL/5M/130V/STD ACC	45	E26	130	390	5 000	30	Flood	15

¹ This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.



Reflector



MOL: 3 7/32 in. (82 mm)
Ø 2 in. (51 mm)

PAR16



MOL: 3 7/32 in. (82 mm)
Ø 2.5 in. (63.5 mm)

PAR20



MOL: 4 7/16 in. (113 mm)
Ø 7 in. (178 mm)

PAR56

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Beam angle (°)	Beam spread	Case qty (master)
PAR16										
50974 ¹	H40PAR16/NFL/2.5M/130V/STD	40	E26	130	400	2 500	2 800	30	Narrow Flood	15
PAR20										
69248	H35PAR20/NFL/2.5M/130V/STD S2	35	E26	130	235	5 000	2 800	28	Narrow Flood	15
PAR56										
43495	Q500PAR56MFL	500	GX16d	120	8 000	4 000	2 950	42	Flood	6
43496	Q500PAR56WFL	500	GX16d	120	8 000	4 000	2 950	66	Wide Flood	6



MOL: 5 5/16 in. (135 mm)
Ø 4 3/4 in. (121 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (master)
PAR38											
10146 ²	H60PAR38/CLB/5M/MS/130V/STD	60	E26	130	800	5 000	2 900	36	Flood	1 700	15

¹ This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.
² This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.

ALR

ALR lamps are halogen aluminium reflector lamps. They are a lightweight and compact light source which are mainly used in display lighting, accent lighting, task lighting and in elevators.



MOL: 1 17/32 in. (39 mm)
Ø 1 1/2 in. (38 mm)

ALR12

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Finish	Beam angle (°)	Beam spread	Case qty (inner/master)
ALR12 - Cover Glass											
55062	20ALR12/F/FL/BA15d/12V/GBF STD	20	BA15d	12	750	2 000	3 000	Frost	32	Flood	20/100



dimnable