



SKU: GMS-4

UPC: 0783669997279

Features & Benefits:

Description:Permaground Copper Ground Clamp to Surface, Conductor Range 500-300, 1 Conductor, 1 Bolt, 1/2in Bolt Size, Single Plate

Specs

Additional Class Attributes

| | |
|----------------------------|------------|
| Connection | Mechanical |
| Number of Conductors | 1 |
| Number of Ports / Wireways | 1 |
| Wire Orientation | Parallel |

Dimensions

| | |
|--------------------------------|--------------|
| Drive Size Main | 1/2 |
| Drive Type Main | External Hex |
| Height (IN) | 2.614 |
| Height BX (IN) | 5 |
| Height (mm) | 66.3956 |
| Length (IN) | 2.298 |
| Length (mm) | 58.3692 |
| Mounting Bolt/Stud Length | 2.614 |
| Mounting Bolt/Stud Length (mm) | 66.3956 |
| Weight (LB) | 0.5 |
| Weight BX (LB) | 25.41 |
| Width (IN) | 1.4 |
| Width BX (IN) | 6.5 |
| Width (mm) | 35.56 |

Material and Finish

| | |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish | NA |
| Insulation | NA |
| Material | Copper |

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

Bolt and Screw Sizes

| | |
|-------------------------|------|
| Clamping Bolt Size | 5/16 |
| Mounting Bolt/Stud Size | 5/16 |

| | |
|--|----|
| Number of Wire Binding Screws per Port | 0 |
| Wire Binding Screw Size | NA |

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 50 |
| Direct Burial | No |
| Dual Rated | No |
| NEMA Code | 0-000-1 |
| UPC Code | 78366999727 |

Testing Standards

| | |
|-------------------|---|
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number | NA |
| UL File Number | NA |

Color

| | |
|-------|--------|
| Color | Copper |
|-------|--------|

Conductor Ranges

| | |
|--|-----------------------|
| Conductor Range AL Solid (Secondary, tap, load) | NA |
| Conductor Range AL Stranded (Primary, run, main, line) | NA |
| Conductor Range AL Stranded (Secondary, tap, load) | NA |
| Conductor Range CU Solid (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Secondary, tap, load) | NA |
| Conductor Range CU Stranded (Primary, run, main, line) | 500 kcmil - 300 kcmil |
| Conductor Range CU Stranded (Secondary, tap, load) | NA |
| Conductor Range AL Solid (Primary, run, main, line) | NA |