

T822K1034

THERMOSTAT – LOW VOLTAGE / 24 V

COLOUR

- white

VOLTAGE

- 1.2 A @ 24 Vac

CONTROL

- two-wire connection
- all or nothing (on/off) @ 24 Vac
- compatible with all RE, RM and R841 model relays
- temperature in degrees Celsius

TEMPERATURE RANGE

- 10 to 30 °C (50 to 86 °F)

WARRANTY

- one year



PRODUCT	DESCRIPTION	PRICE
T822K1034	LOW VOLTAGE THERMOSTAT (24 V)	54.00

DIMENSIONS: 2.83 in. x 4.75 in. x 1.46 in. (71.9 mm x 120.7 mm x 37.1 mm)



T87K1015

THERMOSTAT – LOW VOLTAGE / 24 V

COLOUR

- white

VOLTAGE

- 1 A @ 24 Vac

CONTROL

- two-wire connection
- all or nothing (on/off) @ 24 Vac
- compatible with all RE, RM and R841 model relays
- temperature in degrees Celsius

TEMPERATURE RANGE

- 10 to 30 °C (50 to 86 °F)

WARRANTY

- one year



PRODUCT	DESCRIPTION	PRICE
T87K1015	LOW VOLTAGE THERMOSTAT (24 V)	112.00

DIMENSIONS: 3 11/16 in. diameter x 1 3/4 in. (93.7 mm diameter x 44.5 mm)



°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products.
For all the latest models and prices, please refer to our website at www.stelpro.com.