



30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Metal Operator, Round Non-Illuminated Selector Switch, Short Lever Black with White Insert 2 Position, A-CAM Spring Return from Right UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

|                                           |                 |
|-------------------------------------------|-----------------|
| design of the product                     | Actuator round  |
| <b>Enclosure</b>                          |                 |
| number of command points                  | 1               |
| delivery state as a kit                   | No              |
| <b>Actuator</b>                           |                 |
| design of the actuating element           | selector switch |
| color of the actuating element            | white           |
| material of the actuating element         | plastic         |
| type of unlocking device                  | without         |
| number of switching positions             | 2               |
| <b>Front ring</b>                         |                 |
| product component front ring              | Yes             |
| design of the front ring                  | standard        |
| material of the front ring                | metal           |
| color of the front ring                   | chrome          |
| <b>Holder</b>                             |                 |
| material of the holder                    | Metal           |
| <b>General technical data</b>             |                 |
| product component                         |                 |
| • light source                            | No              |
| degree of pollution                       | 1               |
| protection class IP                       | IP66            |
| operating frequency maximum               | 600 1/h         |
| Weight                                    | 0.12 kg         |
| <b>Ambient conditions</b>                 |                 |
| ambient temperature                       |                 |
| • during operation                        | -35 ... +70 °C  |
| • during storage                          | -40 ... +85 °C  |
| <b>Installation/ mounting/ dimensions</b> |                 |
| shape of the installation opening         | round           |
| <b>Further information</b>                |                 |

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2ACB>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2ACB>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2ACB>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SA2ACB&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2ACB&lang=en)

---

last modified:

5/31/2021 