

Breaker BQD 1P 70A 347VAC 10kA CSA

| General technical data | |
|---|-----------------------------|
| number of poles | 1 |
| suitability for operation | CONSTRUCTION |
| Electricity | |
| continuous current rated value | 70 A |
| supply voltage frequency rated value 50/60 Hz | Yes |
| Environmental conditions | |
| ambient temperature during operation maximum | 40 °C |
| Model | |
| product brand name | Siemens |
| special product feature | PANELBOARD MOUNT |
| type of electrical connection | LOW TAB |
| Mechanical Design | |
| depth [in] | 4 in |
| design of the overload release | THERMAL MAGNETIC TRIP UNIT |
| design of the product | BQD |
| height [in] | 1 in |
| material of the enclosure | MOLDED CASE CIRCUIT BREAKER |
| size of the circuit-breaker | 100A |
| width [in] | 3 in |
| General product approval | |
| standard | UL 489 CSA-C22.2 |
| General Product Approval | EMV |



[Confirmation](#)



[Miscellaneous](#)



| Test Certificates | Marine / Shipping |
|-------------------|-------------------|
|-------------------|-------------------|

[Special Test Certificate](#)

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)



| Marine / Shipping | other | Dangerous goods |
|-------------------|-------|-----------------|
|-------------------|-------|-----------------|



[CCS \(China Classification Society\)](#)

[Confirmation](#)

[Miscellaneous](#)

[Miscellaneous](#)

[Transport Information](#)

| Environment |
|-------------|
|-------------|

[Environmental Confirmations](#)



[Environmental Confirmations](#)

last modified:

12/20/2023 

