

Eaton FWJ-80A

Catalog Number: FWJ-80A

Eaton Bussmann series FWJ high speed fuse, 80A, 25 kAIC (35-200A), 100 kAIC (250-2000A), 50 kAIC at 800 Vdc (35-200A, 450-600A), None, High speed fuse, Blade end X blade end, Stud

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWJ-80A
	UPC
	051712796170
EAN	Product Length/Depth
5027590499880	126 mm
Product Height	Product Width
29 mm	29 mm
Product Weight	Warranty
195.4 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	CSA Certified UL Recognized



Product specifications

Rated voltage DC

800 V

Interrupt rating

450-600A)

25 kAIC (35-200A)

50 kAIC at 800 Vdc (35-200A)

100 kAIC (250-2000A)

Center-to-center distance of connections

109.14 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC/DC

Mounting method

Stud

Amperage Rating

800 A

Fuse type

FWJ-A

Rated switching capacity

25 A

Voltage rating

1000 Vac, 800 Vdc

Fuse indicator

Non Indicating

Construction size

Other

Clearing (I2T)

9700 at 1000 V

Rated voltage AC

1000 V

Color

None

Connection

Blade end x blade end

Mounting dimension

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Specifications and datasheets

[Eaton Specification Sheet - FWJ-80A](#)

M8

Utilization category

aR (accompanied semiconductor protection)

Watt losses

13 W

Type

High speed fuse

Fuse shape

Center bolted tags

Breaking capacity

25 kA

Class

Class aR

Pre arc (I²T)

1550

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia