# Eaton FWP-20A22FI

# Catalog Number: FWP-20A22FI

Eaton Bussmann series FWP high speed fuse, 700 Vac, 700 Vdc (UL), 20A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, With Indicator, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceremic - FWP-20A22FI

# General specifications

**Product Name** 

Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWP-20A22FI

**UPC** 

051712510752

Product Length/Depth

**EAN** 

5027590500326

58 mm

**Product Height** 

23 mm

**Product Width** 

23 mm

**Product Weight** 

61.7 g

Warranty

Not Applicable

Compliances

Certifications

CE Marked RoHS Compliant

**UL** Recognized



**Product specifications** Interrupt rating 200 kAIC Release characteristic Other Amperage Rating 20 A Frequency rating - max 62 Hz Fuse type FWP-A22FI Accessories JM70100 Fuse base Fitted with: Striker Fuse size 22 x 58 mm Voltage rating 500 V Fuse indicator Top fuse status indicator Construction size 22 mm x 58 mm Clearing (I2T) 330 Color White Connection Ferrule end x ferrule end Quantity 10 Material Ceramic Utilization category

aR (accompanied semiconductor protection)

Watt losses

## Resources

### Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-\*A10F,FWH-\*A14F,FWP-\*A14F,FWP-\*A14FI etc

UKCA FWC-\*A10F,FWH-\*A14F,FWP-\*A14F,FWP-\*A14FI etc

Specifications and datasheets

Eaton Specification Sheet - FWP-20A22FI

Type

High speed fuse

Fuse shape

Cylindrical

Used with

Finger safe holders/blocks and striker

Breaking capacity

200 kA

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

23

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia