

Eaton FWS-8A20F

Catalog Number: FWS-8A20F

Eaton Bussmann series high speed traction fuse, 8A, 50 kAIC, Fuse, Class gS

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed traction fuse	FWS-8A20F
	UPC
	051712634588
EAN	Product Length/Depth
5027590501309	127 mm
Product Height	Product Width
20 mm	20 mm
Product Weight	Warranty
93.4 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated



Product specifications

Rated voltage DC

1000 V

Interrupt rating

50 kA at 1000 Vdc

Current type

AC

Suitable for

CH127 Fuse holder

Release characteristic

Other

Amperage Rating

8 A

Frequency rating - max

62 Hz

Fuse type

FWS-A20FI

With striker

No

Fuse size

20 x 127 mm

Voltage rating

1400 V

Construction size

Other

Clearing (I²T)

192 at 750 Vdc

Rated voltage AC

1400 V

Color

None

Material

Ceramic

Mounting dimension

Other

Utilization category

Resources

Catalogs

[Traction fuse-links](#)

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE FWS-*A20F and FWS-*A20FI](#)

[UKCA FWS-*A20F and FWS-*A20FI](#)

Specifications and datasheets

[Eaton Specification Sheet - FWS-8A20F](#)

gL/gG (cable protection/equipment protection)

Watt losses

7.6 W

Type

Fuse

Fuse shape

Cylindrical

Breaking capacity

50 kA

Frequency rating - min

45 Hz

Class

Class gG

Pre arc (I²T)

64

Application

traction

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)