

Eaton FWA-15A10F

Catalog Number: FWA-15A10F

Eaton Bussmann series FWA high speed fuse, 500 Vac (0.25-6.3A), 500 Vdc (2-5A), 15A, 100 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWA-15A10F
	UPC
	051712795210
EAN	Product Length/Depth
5027590499163	45 mm
Product Height	Product Width
23 mm	63 mm
Product Weight	Warranty
9.2 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	CSA Certified UL Recognized



Product specifications

Fuse indicator

Other

Interrupt rating

100 kAIC

Construction size

10 x 38 mm

Clearing (I2T)

50

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

15 A

Frequency rating - max

62 Hz

Utilization category

aR (accompanied semiconductor protection)

Watt losses

3.3 W

Fuse type

FWA-A10F

Accessories

BMM Fuse block

CHM modular fuse holder

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

200 kA

Fuse size

10 x 38 mm

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Specifications and datasheets

[Eaton Specification Sheet - FWA-15A10F](#)

Technical data sheets

[720003 FWA](#)

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

14

Voltage rating

150 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia