

Product specifications

Eaton FWA-20A10F

Catalog Number: FWA-20A10F

Eaton Bussmann series FWA high speed fuse, 500V, 20A, 100 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWA-20A10F
UPC	051712795227
EAN	Product Length/Depth
5027590499187	39 mm
Product Height	Product Width
11 mm	11 mm
Product Weight	Warranty
9.2 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	CSA Certified UL Recognized

Product specifications

Fuse indicator

Other

Interrupt rating

100 kAIC

Construction size

10 x 38 mm

Clearing (I₂T)

130

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

20 A

Frequency rating - max

62 Hz

Utilization category

aR (accompanied semiconductor protection)

Watt losses

3.8 W

Fuse type

FWA-A10F

Accessories

BMM Fuse block

CHM modular fuse holder

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

200 kA

Fuse size

10 x 38 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Specifications and datasheets

Eaton Specification Sheet - FWA-20A10F

Technical data sheets

720003 FWA

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I_{2T})

33

Voltage rating

150 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc

Eaton House

30 Pembroke Road

Dublin 4, Ireland

Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia