

Eaton FWX-1200AH

Catalog Number: FWX-1200AH

Eaton Bussmann series FWX high speed fuse, 1200A, 200 kAIC Vac, 50 kAIC at 250 Vdc, None, High speed fuse, Blade end X blade end, Flush

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWX-1200AH
	UPC
	051712795623
EAN	Product Length/Depth
5027590021944	10.2 mm
Product Height	Product Width
7 mm	10.2 mm
Product Weight	Warranty
3 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	UL Recognized CSA Certified

Product specifications

Interrupt rating

50 kAIC at 250 Vdc

200 kAIC Vac

Center-to-center distance of connections

65.8 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Mounting method

Flush

Amperage Rating

10 A

Fuse type

FWX-AH

Rated switching capacity

200 A

Voltage rating

250 Vac, 250 Vdc

Fuse indicator

Non Indicating

Construction size

Other

Clearing (I₂T)

750000 at 250 V

Rated voltage AC

250 V

Color

None

Connection

Blade end x blade end

Mounting dimension

Other

Utilization category

aR (accompanied semiconductor protection)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Specifications and datasheets

Eaton Specification Sheet - FWX-1200AH

Watt losses

103 W

Type

High speed fuse

Fuse shape

Cylindrical, flush end

Breaking capacity

200 kA

Class

Class aR

Pre arc (I_{2T})

92000

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia