

# Eaton FWA-40A21F

Catalog Number: FWA-40A21F

Eaton Bussmann series FWA high speed fuse, 500 Vac/dc (35-800A only), 40A, 100 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end

## General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWA-40A21F
	UPC
	051712795265
EAN	Product Length/Depth
5027590499262	51 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
56.6 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	UL Recognized CSA Certified



## Product specifications

### Fuse indicator

Other

### Interrupt rating

100 kAIC

### Construction size

Other

### Clearing (I<sub>2</sub>T)

1000 at 150 V

### Connection

Ferrule end x ferrule end

### Material

Ceramic

### Release characteristic

Other

### Amperage Rating

40 A

### Frequency rating - max

62 Hz

### Utilization category

aR (accompanied semiconductor protection)

### Watt losses

5.1 W

### Fuse type

FWA-A21F

### Type

High speed fuse

### Fuse shape

Cylindrical

### Breaking capacity

200 kA

### Fuse size

21 x 51 mm

### Frequency rating - min

45 Hz

### Class

## Resources

### Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

### Specifications and datasheets

[Eaton Specification Sheet - FWA-40A21F](#)

### Technical data sheets

[720003 FWA](#)

Class aR

Pre arc (I2T)

100

Voltage rating

150 V

Application

Semiconductor, DC Common bus, DC drives, Power  
converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)