

Eaton FWJ-25A14F

Catalog Number: FWJ-25A14F

Eaton Bussmann series FWJ high speed fuse, 700 Vac/dc, 25A, 20 kAIC
Vac/dc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWJ-25A14F
UPC	051712796118
EAN	Product Length/Depth
5027590499750	90 mm
Product Height	Product Width
39 mm	80 mm
Product Weight	Warranty
26.4 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	UL Recognized



Product specifications

Fuse indicator

Non Indicating

Interrupt rating

25 kAIC

Construction size

14 mm x 51 mm

Clearing (I₂T)

350

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

25 A

Frequency rating - max

62 Hz

Utilization category

aR (accompanied semiconductor protection)

Watt losses

11 W

Fuse type

FWJ-A14F

Accessories

CH14 Modular fuse holder

FW14-PCB

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

25 kA

Fuse size

14 x 51 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Specifications and datasheets

Eaton Specification Sheet - FWJ-25A14F

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I_{2T})

33

Voltage rating

500 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc

Eaton House

30 Pembroke Road
Dublin 4, Ireland

Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia