

Eaton FWJ-30A14F

Catalog Number: FWJ-30A14F

Eaton Bussmann series FWJ high speed fuse, 700 Vac/dc, 30A, 20 kAIC
Vac/dc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWJ-30A14F
	UPC
	051712796125
EAN	Product Length/Depth
5027590499767	60 mm
Product Height	Product Width
40 mm	86 mm
Product Weight	Warranty
27.6 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	UL Recognized



Product specifications

Fuse indicator

Non Indicating

Interrupt rating

25 kAIC

Construction size

14 mm x 51 mm

Clearing (I2T)

450

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

30 A

Frequency rating - max

62 Hz

Utilization category

aR (accompanied semiconductor protection)

Watt losses

14 W

Fuse type

FWJ-A14F

Accessories

CH14 Modular fuse holder

FW14-PCB

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

25 kA

Fuse size

14 x 51 mm

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Specifications and datasheets

[Eaton Specification Sheet - FWJ-30A14F](#)

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

52

Voltage rating

500 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia