Eaton FWP-6A14F

Catalog Number: FWP-6A14F

Eaton Bussmann series FWP high speed fuse, 700V (UL), 6A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

General specifications

Product Name

Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWP-6A14F

UPC

051712677851

Product Width

Product Length/Depth

EAN

5027590501057

Product Height

52 mm

15 mm

15 mm

Product Weight

20.2 g

Warranty

Not Applicable

Compliances

Certifications

Contact factory RoHS Compliant

UL Recognized CSA Certified



Product specifications

Interrupt rating 200 kAIC Release characteristic Other Amperage Rating 63 A Frequency rating - max 62 Hz Fuse type FWP-A14F Fuse size 14 x 51 mm Voltage rating 700 V Fuse indicator Other Construction size 14 mm x 51 mm Color White Connection Ferrule end x ferrule end Quantity 10 Material Ceramic Utilization category aR (accompanied semiconductor protection) Watt losses 2 W Type High speed fuse Fuse shape Cylindrical

Used with

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Specifications and datasheets

Eaton Specification Sheet - FWP-6A14F

Finger safe holders/blocks and striker

Breaking capacity

200 kA

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

2

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia