

Eaton FWL-25A20FI

Catalog Number: FWL-25A20FI

Eaton Bussmann series high speed traction fuse, 25A, 45 kAIC, With Indicator, Fuse, Class gS

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed traction fuse	FWL-25A20FI
	UPC
	051712640343
EAN	Product Length/Depth
5027590500012	127 mm
Product Height	Product Width
20 mm	20 mm
Product Weight	Warranty
104.3 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated



Product specifications

Rated voltage DC

1000 V

Interrupt rating

50 kA at 1000 Vdc

Current type

AC

Suitable for

CH127 Fuse holder

Release characteristic

Other

Amperage Rating

25 A

Frequency rating - max

62 Hz

Fuse type

FWL-A20FI

With striker

Yes

Fuse size

20 x 127 mm

Voltage rating

1200 V

Fuse indicator

With Indicator

Construction size

Other

Clearing (I2T)

2760 at 750 Vdc

Rated voltage AC

1200 V

Color

None

Material

Ceramic

Mounting dimension

Resources

Catalogs

[IEC high speed fuse links](#)

[Traction fuse-links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA FWL-*A20F and FWL-*A20FI](#)

[CE FWL-*A20F and FWL-*A20FI](#)

Specifications and datasheets

[Eaton Specification Sheet - FWL-25A20FI](#)

Other

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

6.5 W

Type

Fuse

Fuse shape

Cylindrical

Breaking capacity

50 kA

Frequency rating - min

45 Hz

Class

Class gG

Pre arc (I²T)

1200

Application

traction

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia