

Eaton FWS-6A20F

Catalog Number: FWS-6A20F

Eaton Bussmann series high speed traction fuse, 6A, 50 kAIC, Fuse, Class gS

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed traction fuse	FWS-6A20F
	UPC
	051712570688
EAN	Product Length/Depth
5027590501286	127 mm
Product Height	Product Width
.001 mm	20 mm
Product Weight	Warranty
96.7 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated



Product specifications

Rated voltage DC

1000 V

Interrupt rating

50 kAIC

50 kA at 1000 Vdc

Current type

DC

Suitable for

CH127 Fuse holder

Release characteristic

Other

Amperage Rating

6 A

Frequency rating - max

62 Hz

Fuse type

FWS-A20FI

With striker

No

Fuse size

20 x 127 mm

Voltage rating

2000 V

Fuse indicator

With Indicator

Construction size

Other

Clearing (I2T)

81 at 750 Vdc

Rated voltage AC

2000 V

Color

None

Material

Ceramic

Resources

Catalogs

[IEC high speed fuse links](#)

[Traction fuse-links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE FWS-*A20F and FWS-*A20FI](#)

[UKCA FWS-*A20F and FWS-*A20FI](#)

Specifications and datasheets

[Eaton Specification Sheet - FWS-6A20F](#)

Mounting dimension

Other

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

6.7 W

Type

Fuse

Fuse shape

Cylindrical

Breaking capacity

50 kA

Frequency rating - min

45 Hz

Class

Class gG

Pre arc (I₂T)

27

Application

traction

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia