

Eaton FWL-20A20F

Catalog Number: FWL-20A20F

Eaton Bussmann series high speed traction fuse, 20A, 45 kAIC, Fuse, Class gS

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed traction fuse	FWL-20A20F
	UPC
	051712570701
EAN	Product Length/Depth
5027590499989	127 mm
Product Height	Product Width
20 mm	20 mm
Product Weight	Warranty
104.2 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated



Product specifications

Rated voltage DC

1000 V

Interrupt rating

50 kA at 1000 Vdc

Current type

AC

Suitable for

CH127 Fuse holder

Release characteristic

Other

Amperage Rating

20 A

Frequency rating - max

62 Hz

Fuse type

FWL-A20F

With striker

No

Fuse size

20 x 127 mm

Voltage rating

1200 V

Construction size

Other

Clearing (I²T)

1550 at 750 Vdc

Rated voltage AC

1200 V

Color

None

Material

Ceramic

Mounting dimension

Other

Utilization category

Resources

Catalogs

[IEC high speed fuse links](#)

[Traction fuse-links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE FWL-*A20F and FWL-*A20FI](#)

[UKCA FWL-*A20F and FWL-*A20FI](#)

Specifications and datasheets

[Eaton Specification Sheet - FWL-20A20F](#)

gL/gG (cable protection/equipment protection)

Watt losses

5.9 W

Type

Fuse

Fuse shape

Cylindrical

Breaking capacity

50 kA

Frequency rating - min

45 Hz

Class

Class gG

Pre arc (I₂T)

675

Application

traction

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)