

Eaton FWS-2A20F

Catalog Number: FWS-2A20F

Eaton Bussmann series high speed traction fuse, 2A, 50 kAIC, Fuse, Class gS

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed traction fuse	FWS-2A20F
	UPC
	051712570671
EAN	Product Length/Depth
5027590501262	127 mm
Product Height	Product Width
.001 mm	20 mm
Product Weight	Warranty
97.4 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated



Product specifications

Rated voltage DC

1000 V

Interrupt rating

50 kAIC

50 kA at 1000 Vdc

Current type

AC

Suitable for

CH127 Fuse holder

Release characteristic

Other

Amperage Rating

2 A

Frequency rating - max

62 Hz

Fuse type

FWS-A20FI

With striker

No

Fuse size

20 x 127 mm

Voltage rating

2000 V

Fuse indicator

With Indicator

Construction size

Other

Clearing (I2T)

2.4 at 750 Vdc

Rated voltage AC

2000 V

Color

None

Material

Ceramic

Resources

Catalogs

[IEC high speed fuse links](#)

[Traction fuse-links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA FWS-*A20F and FWS-*A20FI](#)

[CE FWS-*A20F and FWS-*A20FI](#)

Specifications and datasheets

[Eaton Specification Sheet - FWS-2A20F](#)

Mounting dimension

Other

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

4.4 W

Type

Fuse

Fuse shape

Cylindrical

Breaking capacity

50 kA

Frequency rating - min

45 Hz

Class

Class gG

Pre arc (I₂T)

0.8

Application

traction

Voltage type

AC/DC

Packaging type

Standard