

LED MOOD TAPE KIT

Flexible 4/5/10-Meter (157-1/2" / 196-7/8" / 393-11/16"), Full Color, Indoor/Outdoor – IP65 Accent Lighting

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/Phone		
Notes		

Features

Lighting Performance

Available in 250-450 lumens per meter options, this high density full color (RGB + Tunable White) LED maintains uniform intensity. It provides full color with its RGB channels and full 2200 K to 6500 K whites through the dedicated tunable white channels producing up to 450 lumens per meter at 3500 K.

Color Temperature

Achieves full color, combining RGB and Tunable White (2200 K - 6500 K), with 90+ CRI in the Tunable White range and an R9 of up to 95.

Lumen Maintenance

LEDs reduce ongoing maintenance, has a rated life of over 50,000 hours.

Power Consumption

Operates as a constant voltage load at 24VDC, and consumes up to 0.20 Amps / 6 Watts per meter.

Dimming

The LED tape is Wi-Fi dimmable when used with our OnCloud Adapter, or High Power OnCloud Adapter (sold separately). See page 2 for driver options.

Note: Not compatible with standard dimmers.

Beam Spread

This LED tape features a 120° linear beam spread to provide even light distribution.

Operating Temperature

-20°C~42°C (-4°F~108°F).

Mounting

This flexible LED tape is provided with a 3M® high bond adhesive backing that provides secure mounting to smooth surfaces.

Environment

Suitable for dry, damp and wet locations; tape is IP65 rated. **Note:** For installation in wet locations, do not cut the tape and make all electrical connections in an appropriate enclosure

LED Driver

24V DC driver available as plug-in or hardwire, with a DC 2.1 connector. Drivers feature open and short circuit protection, and over voltage protection.

OnCloud Adapter / High Power OnCloud Adapter

An integrated constant voltage LED driver and a Wi-Fi + Bluetooth controller module. Available in 40W and 96W.

Kit Includes

- Tape at selected length with powerfeed
- LED driver
- 24V 5-channel OnCloud adapter
- DC 2.1 jack low-voltage powerfeed
- Extrusion with lens and end caps (optional)

Note: Connectors sold separately, see accessories below.

Start-Up Kit Includes

- All items in the above kit, plus
- Room Controller
- 2 x Power Feed
- 4 x Jumper
- 10-ft SJT6 AWG20 extension cable



SPECIFICATION	
Application	Undercabinet
Approved location	Wet
Beam Angle	120°
CCT	RGB + Tunable White (2200 K ~ 6500 K)
Certification	cETLus
CRI	90+
Dimming	Yes*
Dimming Technology	Wireless OnCloud
LED Density	180 LEDs/m, groups of 3 (WW/CW/RGB)
Link Connector	TP-CON-12MM6PIN-I-10
Lumens	Up to 450lm/m (140lm/ft)
Lumens per watt	Up to 90
Max. Op. Temp.	42°C (108°F)
Maximum Run	10 meters
Min. Start Temp.	-20°C (-4°F)
Power Supply Type	Constant Voltage
Projected Life	70% @ 50,000 hrs
Voltage	24V DC
Warranty	3 Years
Wattage	Up to 6W per meter

* Not compatible with standard dimmers.



Description

The Mood Tape Kit includes Tape at selected length, LED driver, OnCloud Adapter, low-voltage powerfeed, and extrusion (optional). This LED tape provides ample illumination for residential, retail and commercial accent lighting. Suitable for dry, damp and wet locations.



Cuttable

(Every 4" / 102mm)
Use Silicone (not included) to seal cut end.



Notes: Accessories should be ordered separately. For additional options please consult your Liteline representative. Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Ordering Guide

Length	Wattage	Driver	Lens + Channel ²
TP- [] - MT	[] - OCKIT	[]	[]
0540 : 5-meter, 40W Adapter	03 : 3W/m	1 : Hardwire 2 : Plug-in ¹	Leave blank for no extrusion 1 : LED-TP-AL1607 2 : LED-TP-AL1715SA 3 : LED-TP-AL1715RA
0540 : 5-meter, 40W Adapter 1040 : 10-meter, 40W Adapter	04 : 4W/m		
0440 : 4-meter, 40W Adapter 1098 : 10-meter, 96W High Power Adapter	06 : 6W/m		



¹ Plug-in driver can only be used with 5-meter 40W adapter and 4-meter 40W adapter. ² Appropriate amount will be provided in 2M (6ft) lengths, tape connectors require a gap.


Mood Tape Start-Up Kits (Lens + Channel / Accessories sold separately)



TP-0540-MT03-OCKIT3
5-meter, 3W/m, 40W OnCloud Adapter, 60W Hardwire Driver, Room Controller, 2x Power Feed, 4x Jumper, 10-ft SJT6 AWG20 extension cable.



TP-1098-MT06-OCKIT3
10-meter, 6W/m, 96W High Power OnCloud Adapter, 100W Hardwire Driver, Room Controller, 2x Power Feed, 4x Jumper, 10-ft SJT6 AWG20 extension cable.



Additional Tape



TP-5M03W-RGBTW95A-65
5-Meter roll, 250lm per meter (3W per meter), IP65, 24VDC, RGB and 2200 K - 6500 K.



TP-5M04W-RGBTW95A-65
5-Meter roll, 350lm per meter (4W per meter), IP65, 24VDC, RGB and 2200 K - 6500 K.



TP-10M04W-RGBTW95A65
10-Meter roll, 350lm per meter (4W per meter), IP65, 24VDC, RGB and 2200 K - 6500 K.



TP-4M06W-RGBTW95A-65
4-Meter roll, 450lm per meter (6W per meter), IP65, 24VDC, RGB and 2200 K - 6500 K.



TP-10M06W-RGBTW95A65
10-Meter roll, 450lm per meter (6W per meter), IP65, 24VDC, RGB and 2200 K - 6500 K.

Extrusions




SURFACE MOUNT LED-TP-AL1607

- 7mm deep
- 3W: 105lm/m (32lm/ft)
- 4W: 168lm/m (51lm/ft)
- 6W: 264lm/m (80.5lm/ft)
- Compatible with tape up to 12mm wide
- 2m (6ft)
- Includes end caps

Dot Rendering Scale



Semi-Diffused



SURFACE MOUNT LED-TP-AL1715SA

- 15mm deep
- 3W: 96lm/m (29lm/ft)
- 4W: 154lm/m (47lm/ft)
- 6W: 242lm/m (74lm/ft)
- Compatible with tape up to 12mm wide
- 2m (6ft)
- Includes end caps

Dot Rendering Scale



Mostly Diffused



RECESSED MOUNT LED-TP-AL1715RA

- 15mm deep
- 3W: 96lm/m (29lm/ft)
- 4W: 154lm/m (47lm/ft)
- 6W: 242lm/m (74lm/ft)
- Compatible with tape up to 12mm wide
- 2m (6ft)
- Includes end caps

Dot Rendering Scale



Mostly Diffused



LED-TP-AL1607-EC
End cap for LED-TP-AL1607, 2-pack.



LED-TP-AL1607-MC
Mounting clips for LED-TP-AL1607, 4-pack.

Connectors (Not rated for wet location)



TP-CON-12MM6PIN-F-10
6-Pin 24VDC 5 Amps max. 175mm power feed. For use with TP-xM0xW-RGBTW95A-65. 10 pack.



TP-CON-12MM6PIN-I-10
6-Pin 24VDC 5 Amps max. "I" connector. For use with TP-xM0xW-RGBTW95A-65. 10 pack.



TP-CON-12MM6PIN-P-10
6-Pin 24VDC 5 Amps max. 175mm jumper. For use with TP-xM0xW-RGBTW95A-65. 10 pack.

OnCloud



LC-CRTL-SCENE-1
OnCloud Room Controller, Wi-Fi, On/OFF, CCT, Dimming and favourite scenes.



LC-CRTL-RMT01WIZ-BK
OnCloud multi-function remote control.



LC-DVR-CV96W1MT03-5C
LC-DVR-CV96W1MT04-5C
LC-DVR-CV96W1MT06-5C
40W, 24V 5-Channel OnCloud adapter, controls wireless dimming, white turning, color and on/off capability. Compatible with the WIZ app, Room Controller and smart speakers.



OC-DVR-CV96W1MT03-5C
OC-DVR-CV96W1MT04-5C
OC-DVR-CV96W1MT06-5C
96W, 24V 5-Channel High Power OnCloud adapter, controls wireless dimming, white tuning, color and on/off capability. Compatible with the WIZ app, Room Controller and smart speakers.

Plug-in Drivers (non-dimming)



LED-DVR-24V-36W
LED plug-in driver with DC 2.1 jack, 24V, 36W.



LED-DVR-24V-60W
LED plug-in driver with DC 2.1 jack, 24V, 60W.

Power feed required



LED-HWB-DC21-6-PF
DC 2.1 barrel plug to bare leads power feed.

Indoor Hardwire Drivers (non-dimming)



LED-HWB-24V-36W
LED hardwire driver with DC 2.1 jack, 24V, 36W.



LED-HWB-24V-100W
LED hardwire driver with DC 2.1 jack, 24V, 100W.



LED-HWB-24V-60W
LED hardwire driver with DC 2.1 jack, 24V, 60W.

Power feed required



LED-HWB-DC21-6-PF
DC 2.1 barrel plug to bare leads power feed.

Extension Cable



AW20-RGBTW-SJT6-50
50-ft SJT6 AWG20 extension cable