

Low-Halide Multi-Purpose Polyester Labels (B-569)

Hi-Performance Polyester Tape (B-569) has low halide content and is designed for marking stainless steel pipes particularly in harsh environments.

- Durable, ultra-smooth polyester labels with permanent pressure sensitive acrylic adhesive
- Outdoor grade polyester tape can be thermal transfer printed
- Withstands mild chemicals, oil and water
- Service temperature of -40°F to 212°F (-40°C to 100°C)
- A ribbon is required to print this material.




Figure 33



Figure	Catalog #	B#	Material	Color	Label width A inch (mm)	Roll length B feet (m)	Labels per roll	Rec. ribbon
Fig. 33	M7C-1000-569-WT	B-569	Polyester	White	1.000 (25.4)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-2000-569-WT	B-569	Polyester	White	2.000 (50.8)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-1000-569-YL	B-569	Polyester	Yellow	1.000 (25.4)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-2000-569-YL	B-569	Polyester	Yellow	2.000 (50.8)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-1000-569-BL	B-569	Polyester	Blue	1.000 (25.4)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-2000-569-BL	B-569	Polyester	Blue	2.000 (50.8)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-1000-569-GN	B-569	Polyester	Green	1.000 (25.4)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-2000-569-GN	B-569	Polyester	Green	2.000 (50.8)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-1000-569-RD	B-569	Polyester	Red	1.000 (25.4)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-2000-569-RD	B-569	Polyester	Red	2.000 (50.8)	50 (15.2)	1 roll (cont.)	M7-R10000

Cold Temperature Application Multi-Purpose Polyester Labels (B-549)

Cold Temperature Label Stock (B-549) is a flexible, dimensionally stable, pressure sensitive polyester tape perfect for use in any cold storage warehouse, cooler or freezer.

- Special adhesive can be applied to extremely cold surfaces (-10°F) and withstands temperatures as low as -40°F
- Tape can be thermal transfer printed
- Withstands mild chemicals, oil and water
- Service temperature of -40°F to 212°F (-40°C to 100°C)
- A ribbon is required to print this material. Use Part Number M7-R10000




Figure 33



Figure	Catalog #	B#	Material	Color	Label width A inch (mm)	Roll length B feet (m)	Labels per roll	Rec. ribbon
Fig. 33	M7C-1000-549-WT	B-549	Polyester	White	1.000 (25.4)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-2000-549-WT	B-549	Polyester	White	2.000 (50.8)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-1000-549-YL	B-549	Polyester	Yellow	1.000 (25.4)	50 (15.2)	1 roll (cont.)	M7-R10000
Fig. 33	M7C-2000-549-YL	B-549	Polyester	Yellow	2.000 (50.8)	50 (15.2)	1 roll (cont.)	M7-R10000