

LS-EMSP-AL (150X80) - Device marker



0831621

<https://www.phoenixcontact.com/in/products/0831621>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Device marker, Aluminum label, aluminum color, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, mounting type: screw, rivet, lettering field size: 150 x 80 mm, Number of individual labels: 2



Your advantages

- Aluminum equipment marking for screwing or riveting
- Identification made from metal, high strength in a lightweight design
- Increased durability due to the decoratively anodized surface

Commercial Data

Item number	0831621
Packing unit	5 pc
Minimum order quantity	5 pc
Sales Key	BG2
Product Key	BG241D
Catalog Page	Page 283 (C-3-2019)
GTIN	4046356925709
Weight per Piece (including packing)	138.16 g
Weight per Piece (excluding packing)	135.16 g
Customs tariff number	76169990
Country of origin	CN

LS-EMSP-AL (150X80) - Device marker



0831621

<https://www.phoenixcontact.com/in/products/0831621>

Technical Data

Product properties

Product type	Device marking
Type	Laser sheet

Marking

Number of individual labels	2
-----------------------------	---

Marking technology

Device	1012015 TOPMARK NEO
Printability	Direct laser marking

Mounting

Mounting type	screw, rivet
---------------	--------------

Material specifications

Color	aluminum color
Material	Aluminum
Components	free from silicone, halogen, and cadmium

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Weathering-resistance

Specification	ISO 4892-2:2013-03
Result	Test passed
Test duration	500 h

LS-EMSP-AL (150X80) - Device marker



0831621

<https://www.phoenixcontact.com/in/products/0831621>

Procedure	A
-----------	---

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 225 °C (250 °C)	Test passed

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Specification	ISO 175:2010 (following)
Test duration	168 h

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Salt spray test

Specification	ISO 9227:2012-05
Result	Test passed
Test duration	336 h

High pressure test

Specification	ISO 20653:2013-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-25 °C ... 120 °C (At temperatures above 80 °C there might be a slight change to the material surface)
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Dimensions

Width	160 mm
Length	80 mm
Hole diameter	4.20 mm
Material strength	1.50 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------