

# UM1-TMF (5X5) - Marker for terminal blocks



0830902

<https://www.phoenixcontact.com/pc/products/0830902>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Marker for terminal blocks, Strip, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5 x 5 mm, Number of individual labels: 24



## Your advantages

- The markers, which are supplied in uniform strips, can be printed onto quickly and easily using the BLUEMARK printing systems
- The UM1-TMF ... UM labeling range includes terminal markers for Weidmüller, Wago, ABB (entrelec), CONTA-CLIP, and Klemsan terminal blocks
- The multi-section marking strips are easy to fit and can be easily separated if required
- The markers support multi-line labeling

## Commercial data

Item number	0830902
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BG211C
Catalog page	Page 171 (C-3-2019)
GTIN	4046356910323
Weight per piece (including packing)	1.32 g
Weight per piece (excluding packing)	1.26 g
Customs tariff number	39269097
Country of origin	PL

# UM1-TMF (5X5) - Marker for terminal blocks



0830902

<https://www.phoenixcontact.com/pc/products/0830902>

## Technical data

### Product properties

Product type	Terminal marking
Pitch	5 mm
Type	flat
Area of application	Weidmüller, Wago, ABB, CONTA-CLIP, and Klemsan: Terminal blocks

### Marking

Number of individual labels	24
Number of individual labels per row	12
Number of marker strips	2

### Marking technology

Device	5146464 THERMOMARK CARD
	5147999 BLUEMARK CLED
Ink ribbon	0801371 THERMOMARK-RIBBON 110-TC
Printability	Thermal transfer
	UV LED technology

### Dimensions

Width	5 mm
Length	5 mm
Pitch	5 mm

### Material specifications

RoHS compliant	yes
Color	white
Material	PC
Flammability rating according to UL 94	V2
Components	free from silicone, halogen, and cadmium

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Wipe resistance of inscriptions

Specification	IEC 61010-1:2010-06
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

# UM1-TMF (5X5) - Marker for terminal blocks



0830902

<https://www.phoenixcontact.com/pc/products/0830902>

## Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

## Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

## Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

## Mounting

Mounting type	snapped
---------------	---------

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)