

# LS-EMSP-V4A (75,6X54) - Device marker



0831656

<https://www.phoenixcontact.com/in/products/0831656>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Device marker, Stainless steel label, silver, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, mounting type: screw, rivet, lettering field size: 75.6 x 54 mm, Number of individual labels: 6



## Your advantages

- Stainless steel device marking for screwing or riveting
- Easy-to-clean and permanent identification that also meets stringent hygiene requirements
- High resistance to corrosion, acids, and temperatures

## Commercial data

Item number	0831656
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BG2
Product key	BG241D
Catalog page	Page 282 (C-3-2019)
GTIN	4046356925952
Weight per piece (including packing)	156.1 g
Weight per piece (excluding packing)	148.97 g
Customs tariff number	73269098
Country of origin	CN

## Technical data

### Product properties

Product type	Device marking
Type	Laser sheet

### Marking

Number of individual labels	6
-----------------------------	---

### Marking technology

Device	1012015 TOPMARK NEO
Printability	Direct laser marking

### Mounting

Mounting type	screw, rivet
---------------	--------------

### Material specifications

RoHS compliant	yes
Color	silver
Material	V4A (1.4404; AISI 316L)
Components	free from silicone, halogen, and cadmium

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
---------------	---------------------------------------

#### Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h
Specification	IEC 60068-2-2:2007-07
Result	Test passed
Duration	240 h
Temperature for testing	350 °C

#### Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 225 °C (250 °C)	Test passed

# LS-EMSP-V4A (75,6X54) - Device marker



0831656

<https://www.phoenixcontact.com/in/products/0831656>

## Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Specification	ISO 175:2010 (following)
Test duration	168 h

## Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05 (following)
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

## Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

## Salt spray test

Specification	ISO 9227:2017-03
Result	Test passed
Test duration	336 h

## Ambient conditions

Ambient temperature (operation)	-80 °C ... 350 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	24 months

## Dimensions

Dimensional drawing	
Width	85 mm
Length	53.7 mm
Hole diameter	3.20 mm
Material strength	0.50 mm

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------