

TMC 83C 15A - Thermomagnetic device circuit breaker



2907618

<https://www.phoenixcontact.com/in/products/2907618>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Thermomagnetic device circuit breaker, number of positions: 3, cross section: 1 mm²- 35 mm², AWG: 18 - 2, fuse type: Automatic device, mounting type: DIN rail: 35 mm

Commercial data

Item number	2907618
Packing unit	4 pc
Minimum order quantity	4 pc
Sales key	*****
Product key	CLA125
GTIN	4055626215921
Weight per piece (including packing)	404.625 g
Weight per piece (excluding packing)	398 g
Customs tariff number	85362010
Country of origin	CN

TMC 83C 15A - Thermomagnetic device circuit breaker



2907618

<https://www.phoenixcontact.com/in/products/2907618>

Technical data

Product properties

Type	DIN rail module, one-piece
Product type	Thermomagnetic device circuit breakers
Product family	TMC 8
Number of positions	3
Mechanical service life	20000

Electrical properties

Fuse type	Automatic device
Service life electrical	6000


General

Operating voltage	240 V AC (277/480Y, 240D)
Rated current I_N	15 A
Tripping method	TM (thermomagnetic)
Rated short-circuit switching capacity I_{cn}	10 kA (IC)
Fuse	C

Connection data

Conductor cross section rigid	1 mm ² ... 35 mm ²
Cross section AWG	18 ... 2 (converted acc. to IEC)
Conductor cross section flexible	1 mm ² ... 35 mm ²
Connection method	Screw connection
Tightening torque, min	2 Nm
Conductor cross section flexible max.	35 mm ²
Conductor cross section, rigid max.	35 mm ²

Dimensions

Dimensional drawing	
Width	52.9 mm
Height	116 mm
Depth	65.7 mm

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-35 °C ... 70 °C
Humidity test	48 h, 95% RH, 40°C (IEC 60068-2-78)
Shock (operation)	30g (11 ms) (IEC 60068-2-11)

TMC 83C 15A - Thermomagnetic device circuit breaker



2907618

<https://www.phoenixcontact.com/in/products/2907618>

Vibration (operation)	±0.38 mm (10-57 Hz), 5g (57...500 Hz) (IEC 60068-2-6, Fc, sine)
-----------------------	---

Standards and regulations

Standards/specifications	UL 489
	IEC 60947-2

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in