

TMC 82D 25A - Thermomagnetic device circuit breaker



2907666

<https://www.phoenixcontact.com/in/products/2907666>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Thermomagnetic device circuit breaker, number of positions: 2, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: DIN rail: 35 mm



Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 2907666 |
| Packing unit | 1 pc |
| Minimum order quantity | 6 pc |
| Sales key | ***** |
| Product key | CLA125 |
| GTIN | 4055626215723 |
| Weight per piece (including packing) | 222.222 g |
| Weight per piece (excluding packing) | 222.222 g |
| Customs tariff number | 85362010 |
| Country of origin | CN |

TMC 82D 25A - Thermomagnetic device circuit breaker



2907666

<https://www.phoenixcontact.com/in/products/2907666>

Technical data

Product properties

| | |
|-------------------------|--|
| Type | DIN rail module, one-piece |
| Product type | Thermomagnetic device circuit breakers |
| Product family | TMC 8 |
| Number of positions | 2 |
| Mechanical service life | 20000 |

Electrical properties

| | |
|-------------------------|------|
| Service life electrical | 6000 |
|-------------------------|------|

General

| | |
|---|---|
| Operating voltage | 240 V AC (277/480Y, 240D) 125 V DC (two poles in series) |
| Rated current I_N | 25 A |
| Tripping method | TM (thermomagnetic) |
| Rated short-circuit switching capacity I_{cn} | 10 kA (IC) |
| Fuse | D |

Connection data

| | |
|---------------------------------------|--|
| Conductor cross section rigid | 1 mm ² ... 35 mm ² |
| Cross section AWG | 18 ... 2 (converted acc. to IEC) |
| Conductor cross section flexible | 1 mm ² ... 35 mm ² |
| Connection method | Screw connection |
| Tightening torque, min | 2 Nm |
| Conductor cross section flexible max. | 35 mm ² |
| Conductor cross section, rigid max. | 35 mm ² |

Dimensions

| | |
|---------------------|---------|
| Dimensional drawing | |
| Width | 35.3 mm |
| Height | 116 mm |
| Depth | 65.7 mm |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-------------------------------------|
| Ambient temperature (operation) | -35 °C ... 70 °C |
| Humidity test | 48 h, 95% RH, 40°C (IEC 60068-2-78) |
| Shock (operation) | 30g (11 ms) (IEC 60068-2-11) |

TMC 82D 25A - Thermomagnetic device circuit breaker



2907666

<https://www.phoenixcontact.com/in/products/2907666>

| | |
|-----------------------|---|
| Vibration (operation) | ±0.38 mm (10-57 Hz), 5g (57...500 Hz) (IEC 60068-2-6, Fc, sine) |
|-----------------------|---|

Standards and regulations

| | |
|--------------------------|-------------|
| Standards/specifications | UL 489 |
| | IEC 60947-2 |

Mounting

| | |
|---------------|-----------------|
| Mounting type | DIN rail: 35 mm |
|---------------|-----------------|

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in