

Quality Products. Service Excellence.

Horizontal Finger Cable Manager RB-HFM-OS Series

REPLACED BY THE RB-HFM SERIES



Note: This product line has been discontinued as a stocked series. Information is for reference only. It has been replaced with **RB-HFM Series**. For alternative solution assistance, **contact Hammond here** or call: USA (716) 630-7030, Canada and International (519) 822-2960.

Features



- · Metal components constructed in 16-gauge steel.
- Three (3) inch length fingers constructed in black plastic.
- Snap-on, hinged door.
- Includes cutouts at rear for cable pass-through.
- Fits standard EIA compliant mounting rails.
- Metal components finished in textured RAL9005 black powder paint.
- · Requires mounting hardware.
- RoHS and REACH compliant.







For a double-sided manager, install two (2) managers mounted back-to-back. The rear opening provides a cable pass-thru.

Part of the Rack Basics® line of economy rack solutions.

Accessories



Mounting Hardware

Hook and Loop Roll





	Overall Dinmensions			Usable Mounting Dimensions		
Part No.	Height	Width	Depth	Rack Units	Height	
RB-HFM1	1.72	19.00	4.37	1U	1.75	
RB-HFM2	3.22	19.00	4.37	2U	3.50	

Note that two (2) of the RB-HFM1 cannot be installed on top of each other as the hinged door clip will interfere with the other unit.

Estimated Cable Fill Capacities

Rack		Recommended Ca	able Fill (50% Fill Ratio)	Maximum Cable Fill (100% Fill Ratio)	
Units	Description	Cat 6	Cat 6a	Cat 6	Cat 6a
1U	Channel Opening	20	14	40	28

Rack		Recommended Ca	able Fill (50% Fill Ratio)	Maximum Cable Fill (100% Fill Ratio)	
Units	Description	Cat 6	Cat 6a	Cat 6	Cat 6a
	Finger Opening	18	12	35	24
	Rear Pass Through	20	14	40	28
2U	Channel Opening	49	34	99	69
	Finger Opening	18	12	35	24
	Rear Pass Through	39	27	77	54

Data subject to change without notice

© 2023. Hammond Manufacturing Ltd. All rights reserved.