

# Eaton 1251E-8513

Catalog Number: 1251E-8513

Eaton Enhanced 50 Series Photoelectric Sensor, Sensor distance: 500 Ft., Iso SS Relay, 300 mA at 240 Vac/Vdc, 6.6 Ft. (2m) Cable, 12–240 Vdc 24–240 Vac input, Reverse polarity, short circuit and overload, Yes, Thu-Beam, 6.6 Ft. (2m)

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton Enhanced 50 photoelectric sensor	1251E-8513
<b>UPC</b>	<b>Product Length/Depth</b>
782116112906	1.91 in
<b>Product Height</b>	<b>Product Width</b>
3.46 in	1.81 in
<b>Product Weight</b>	<b>Warranty</b>
0.5375 lb	3 year
<b>Compliances</b>	<b>Certifications</b>
Contact Manufacturer CE Marked	CSA Certified

## defaultTaxonomyAttributeLabel

### Contact Rating

300 mA at 240 Vac/Vdc

### Cable type

Polyvinyl Chloride (PVC)

### Enclosure material

Fiberglass reinforced plastic

### Operating mode

Thru-beam

### Connection

6.6 ft (2 m) cable

### Contact configuration

Isolated solid state relay

### Sensor type

Through beam

### Switch type

Photoelectric

### Input voltage

12-240 Vdc, 24-240 Vac

### LED indicator

Output status: green

Power on: yellow

Marginal gain: red

### Protection

Reverse polarity and short circuit protected

### Time delay

Yes

### Cord length

79.2 ft

### Maximum AC current

300 mA

### Maximum DC current

300 mA

### Operating temperature - max

131 °F

### Operating temperature - min

## Resources

### Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

### Specifications and datasheets

[Eaton Specification Sheet - 1251E-8513](#)

-13 °F

Environmental rating

IP67, IP69K

---



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)