Product specifications

Eaton 1551E-6514

Catalog Number: 1551E-6514

Eaton Enhanced 50 Series Photoelectric Sensor, Photoelectric, Sensor dist. Depends on the fiberoptic cables used, 3A max AC, SPDT Form C Relay, 3A at 240 Vac, 6.6 Ft. (2m) Cable, 12–240 Vdc 24–240 Vac input, Fiberoptic, Visible Red



General specifications

Product Name	**Catalog Number**
Eaton Enhanced 50 photoelectric sensor	1551E-6514
UPC	**Product Length/Depth**
782116112111	1.91 in
Product Height	**Product Width**
3.46 in	1.81 in
Product Weight	**Warranty**
0.5375 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	CSA Certified

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Contact Rating

3A at 240 Vac

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Fiberglass reinforced plastic

Operating mode

Fiber-optic

Visible red

Connection

6.6 ft (2 m) cable

Contact configuration

SPDT form C relay

Sensor type

Fiberoptic

Switch type

Photoelectric

Input voltage

12-240 Vdc, 24-240 Vac

LED indicator

Marginal gain: red

Power on: yellow

Output status: green

Cord length

79.2 ft

Maximum AC current

3 A

Operating temperature - max

131 °F

Operating temperature - min

-13 °F

Environmental rating

IP67, IP69K

Resources

Catalogs

Eaton's Volume 8—Sensing Solutions

Specifications and datasheets

Eaton Specification Sheet - 1551E-6514



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia