

Eaton 1551E-8513

Catalog Number: 1551E-8513

Eaton Enhanced 50 Series Photoelectric Sensor, Sensor dist. depends on the fiberoptic cables, Iso SS Relay, 300 mA at 240 Vac/Vdc, 6.6 Ft.(2m) Cable, 12–240 Vdc 24–240 Vac input, Reverse polarity, short circuit and overload, Visible Red

General specifications



Product Name	Catalog Number
Eaton Enhanced 50 photoelectric sensor	1551E-8513
UPC	Product Length/Depth
782116112142	1.91 in
Product Height	Product Width
3.46 in	1.81 in
Product Weight	Warranty
0.5375 lb	3 year
Compliances	Certifications
Contact Manufacturer	CSA Certified

defaultTaxonomyAttributeLabel

Contact Rating

300 mA at 240 Vac/Vdc

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Fiberglass reinforced plastic

Operating mode

Fiber-optic

Visible red

Connection

6.6 ft (2 m) cable

Contact configuration

Isolated solid state relay

Sensor type

Fiberoptic

Switch type

Photoelectric

Input voltage

12-240 Vdc, 24-240 Vac

LED indicator

Output status: green

Power on: yellow

Marginal gain: red

Protection

Reverse polarity and short circuit protected

Time delay

Yes

Cord length

79.2 ft

Maximum AC current

300 mA

Maximum DC current

300 mA

Operating temperature - max

131 °F

Resources

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - 1551E-8513](#)

Operating temperature - min

-13 °F

Environmental rating

IP67, IP69K



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)