

# Eaton 1551E-6503

Catalog Number: 1551E-6503

Eaton Enhanced 50 Series Photoelectric Sensor, Sensor dist. depends on the fiberoptic cables, Iso SS Relay, 300 mA at 240 Vac/Vdc, 4 Pin Mini Connector, 12–240 Vdc 24–240 Vac input, Reverse polarity, short circuit/overload, Visible Red

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton Enhanced 50 photoelectric sensor	1551E-6503
<b>UPC</b>	<b>Product Length/Depth</b>
782116112234	1.91 in
<b>Product Height</b>	<b>Product Width</b>
4.16 in	1.81 in
<b>Product Weight</b>	<b>Warranty</b>
0.3375 lb	3 year
<b>Compliances</b>	<b>Certifications</b>
Contact Manufacturer CE Marked	CSA Certified

## defaultTaxonomyAttributeLabel

### Contact Rating

300 mA at 240 Vac/Vdc

### Enclosure material

Fiberglass reinforced plastic

### Operating mode

Visible red

Fiber-optic

### Connection

4-pin mini connector

### Contact configuration

Isolated solid state relay

### Sensor type

Fiberoptic

### Switch type

Photoelectric

### Input voltage

12-240 Vdc, 24-240 Vac

### LED indicator

Output status: green

Marginal gain: red

Power on: yellow

### Protection

Reverse polarity and short circuit protected

### Maximum AC current

300 mA

### Maximum DC current

300 mA

### Operating temperature - max

131 °F

### Operating temperature - min

-13 °F

### Environmental rating

IP67, IP69K

## Resources

### Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

### Specifications and datasheets

[Eaton Specification Sheet - 1551E-6503](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)