

Eaton 1551E-8537

Catalog Number: 1551E-8537

Eaton Enhanced 50 Series Photoelectric Sensor, dist. depends on the fiberoptic cables, 250 mA max DC, NPN/PNP Open Collector, 250 mA at 40 Vdc, 4 Pin M12 Pigtail Connector, 10-40 Vdc input, short circuit/overload, Visible Red

General specifications



Product Name	Catalog Number
Eaton Enhanced 50 photoelectric sensor	1551E-8537
UPC	Product Length/Depth
782116112265	1.91 in
Product Height	Product Width
3.46 in	1.81 in
Product Weight	Warranty
0.3375 lb	3 year
Compliances	Certifications
Contact Manufacturer CE Marked	CSA Certified

defaultTaxonomyAttributeLabel

Contact Rating

250 mA at 40 Vdc

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Fiberglass reinforced plastic

Operating mode

Visible red

Fiber-optic

Connection

4-pin M12 pigtail connector

Contact configuration

NPN and PNP open collector

Sensor type

Fiberoptic

Switch type

Photoelectric

Input voltage

10-40 Vdc

LED indicator

Output status: green

Marginal gain: red

Power on: yellow

Protection

Reverse polarity and short circuit protected

Time delay

Yes

Cord length

6 ft

Maximum DC current

250 mA

Operating temperature - max

131 °F

Operating temperature - min

-13 °F

Resources

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - 1551E-8537](#)

Environmental rating

IP67, IP69K



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)