

Eaton 1550E-8507

Catalog Number: 1550E-8507

Eaton Enhanced 50 Series Photoelectric Sensor, dist. depends on the fiberoptic cables, 250 mA max DC, 250 mA at 40 Vdc, 4 Pin Mini Connector, 10-40 Vdc input, short circuit and overload, Infrared, NPN and PNP Open Collector

General specifications



Product Name	Catalog Number
Eaton Enhanced 50 photoelectric sensor	1550E-8507
UPC	Product Length/Depth
782116112425	1.91 in
Product Height	Product Width
4.16 in	1.81 in
Product Weight	Warranty
0.3375 lb	3 year
Compliances	Certifications
Contact Manufacturer	CSA Certified

defaultTaxonomyAttributeLabel

Contact Rating

250 mA at 40 Vdc

Enclosure material

Fiberglass reinforced plastic

Operating mode

Fiber-optic

Infrared

Connection

4-pin mini connector

Contact configuration

NPN and PNP open collector

Sensor type

Fiberoptic

Switch type

Photoelectric

Input voltage

10-40 Vdc

LED indicator

Marginal gain: red

Output status: green

Power on: yellow

Protection

Reverse polarity and short circuit protected

Time delay

Yes

Maximum DC current

250 mA

Operating temperature - max

131 °F

Operating temperature - min

-13 °F

Environmental rating

IP67, IP69K

Resources

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - 1550E-8507](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)