


Eaton C25DND215B

Catalog Number: C25DND215B

Eaton definite purpose contactor, Quick, 15A, 208-240 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 15A, Contactor, Two-pole, 20A, Screw/pressure plate and quick connect terminals (side-by-side), Non-reversing



General specifications

Product Name	Catalog Number
Eaton definite purpose contactor	C25DND215B
UPC	Product Length/Depth
782116307678	3.35 in
Product Height	Product Width
3.75 in	2.4 in
Product Weight	Warranty
1.19 lb	1 year
Compliances	Certifications
RoHS Compliant	UL Recognized CSA Certified

defaultTaxonomyAttributeLabel

Amperage Rating

15A

Number Of Poles

Two-pole

Type

Non-reversing

Coil

208-240 Vac

Coil voltage

50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

15 A

Model

Contactors

Resistive load

20 A

Terminals

Screw/pressure plate and quick connect terminals (side-by-side)

Connection

Quick

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[C25DND2 2D Drawing Xchange](#)

[C25DND2 2D PDF](#)

[C25DND2 AutoCAD 2D Footprint \(mm\)](#)

[C25DND2 AutoCAD 2D Footprint](#)

[C25DND2 3D Inventor](#)

[C25DND2 3D Model Xchange](#)

Specifications and datasheets

[Eaton Specification Sheet - C25DND215B](#)