

Eaton C25DRJ250A

Catalog Number: C25DRJ250A

Eaton definite purpose contactor, Quick, 40A, 110-120 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 40A, Contactor, Four-pole, 50A, Screw/pressure plate and quick connect terminals (side-by-side), Non-reversing



General specifications

Product Name	Catalog Number
Eaton definite purpose contactor	C25DRJ250A
UPC	Product Length/Depth
782116483310	3.35 in
Product Height	Product Width
3.75 in	2.4 in
Product Weight	Warranty
1.19 lb	1 year
Compliances	Certifications
RoHS Compliant	UL Recognized
	CSA Certified
	UL Listed file E1491 (Guide Number NLDX2)

defaultTaxonomyAttributeLabel

Amperage Rating

50A

Number Of Poles

Two-pole

Options

Global listed

Type

Non-reversing

Auxiliary contacts

Quick connect (vertical in-line)

Coil

24 Vac, 50/60 Hz

Enclosure

Open with DIN rail mounting adapter

Frame size

15-50 A, two-pole and three-pole

Inductive full load

50 A

Model

Contactors

Resistive load

65 A

Series

D1

Terminals

Box lugs (posidrive setscrew)

Connection

Quick

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[C25DRJ2 AutoCAD 2D Footprint \(mm\)](#)

[C25DRJ2 3D Inventor](#)

[C25DRJ2 2D PDF](#)

[C25DRJ2 3D Model Xchange](#)

[C25DRJ2 2D Drawing Xchange](#)

[C25DRJ2 AutoCAD 2D Footprint](#)

Specifications and datasheets

[Eaton Specification Sheet - C25DRJ250A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia