

Eaton C25FNF275T

Catalog Number: C25FNF275T

Eaton definite purpose contactor, Quick, 120A, 110-120 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 120A, Contactor, Three-pole, 120A, two- and three-pole, 140A, Box lugs (posidrive setscrew), Non-reversing

General specifications



Product Name	Catalog Number
Eaton definite purpose contactor	C25FNF275T
UPC	Product Length/Depth
782114623503	3.97 in
Product Height	Product Width
3.75 in	2.63 in
Product Weight	Warranty
2.66 lb	1 year
Compliances	Certifications
RoHS Compliant	CSA Certified UL Recognized

defaultTaxonomyAttributeLabel

Amperage Rating

50A

Number Of Poles

Three-pole

Type

Non-reversing

Coil

110-120 Vac, 50/60 Hz

Contact configuration

1 NO

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

50 A

Model

Contactors

Resistive load

65 A

Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

C25FNF2 3D Model Xchange

C25FNF2 3D Inventor

C25FNF2 2D Drawing Xchange

C25FNF2 2D PDF

C25FNF2 AutoCAD 2D Footprint (mm)

Specifications and datasheets

Eaton Specification Sheet - C25FNF275T



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)