

Eaton P60G11S2530CUB

Catalog Number: P60G11S2530CUB

Eaton Mini-Power center, 25 kVA, 1PH 600V to 120/240V Bolt-on breakers, Copper Windings 30 spaces



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Mini-Power center	P60G11S2530CUB
UPC	Product Length/Depth
786680226090	14.58 in
Product Height	Product Width
43.37 in	20.41 in
Product Weight	Warranty
385 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
NAFTA	ANSI
	UL Listed
	CSA Certified
	IEEE Certified

Physical Attributes

Coil material

Copper

Enclosure

NEMA 3R

Frame

310

Insulation

180 °C

Mounting

Wall Mount

Tap size

2 at -5% FCBN

Type

Mini-power center

Wiring connection

M60G11KB

Performance Ratings

Frequency rating

60 Hz

kVA

25 kVA

Kva Rating

25 kVA

Phase

Single-phase

Primary voltage

600 V

Secondary Voltage

120/240 V

Sound Level

NEMA ST-20

Temperature rise

115 °C rise

Volt ampere rating

25 kVA

Miscellaneous

Modification 1

NEMA 3R

Weathershield

Not required

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Multimedia

[Eaton's Transformer Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - P60G11S2530CUB](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)