

Eaton C25END440A

Catalog Number: C25END440A

Eaton definite purpose contactor, Quick, 60A, 24 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 60A, Contactor, Two-pole, 75A, Box lugs (posidrive setscrew) and quick connect terminals , Non-reversing

General specifications



Product Name	Catalog Number
Eaton definite purpose contactor	C25END440A
UPC	Product Length/Depth
782113565309	3.38 in
Product Height	Product Width
3.75 in	2.68 in
Product Weight	Warranty
2 lb	1 year
Compliances	Certifications
RoHS Compliant	UL Recognized CSA Certified

Catalog Notes

Resistive Load rating per pole

defaultTaxonomyAttributeLabel

Amperage Rating

30A

Number Of Poles

Four-pole

Type

Non-reversing

Coil

110-120 Vac, 50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

30 A

Model

Contactors

Resistive load

40 A

Terminals

Box lugs (posidrive setscrew)

Connection

Quick

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Eaton Specification Sheet - C25END440A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)