

Eaton E58-30TD250-GLP-FC

Catalog Number: E58-30TD250-GLP-FC

Eaton harsh-duty sensor, E58 Tubular 30mm Photoelectric Sensor, 1.18 dia, dist. 800 Ft., AC: L1 Switched, 300 mA, 3-Wire, 4 Pin Pigtail Dual Key Micro Connector, 20-132 Vac 50/60 Hz or 15-30 Vdc input, Latching short circuit, Thru-Beam

General specifications



Product Name

Eaton harsh-duty sensor

Catalog Number

E58-30TD250-GLP-FC

UPC

782114091715

Product Length/Depth

1.18 in

Product Height

4.36 in

Product Width

1.18 in

Product Weight

0.2688 lb

Warranty

3 year

Certifications

UL Listed

cUL Listed

CE



Powering Business Worldwide

defaultTaxonomyAttributeLabel

Contact Rating

300 mA DC NPN / 300 mA AC 3 - Wire

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Stainless steel

Operating mode

Thru-beam

Connection

4-pin pigtail dual key micro connector

Contact configuration

DC: NPN open collector

AC: L1 switched

Sensor type

Through beam

Switch type

Photoelectric

Input voltage

20-132 Vac at 50/60 Hz, 15-30 Vdc

LED indicator

Output status: red

Protection

Latching short circuit

Cord length

7 in

Maximum AC current

300 mA

Maximum DC current

300 mA

Operating temperature - max

131 °F

Operating temperature - min

-40 °F

Environmental rating

NEMA 1, NEMA 2, NEMA 3, NEMA 3R, NEMA 3S, NEMA 4,

Resources

Brochures

[Test the Best Photoelectric Sensors: E58 Series Harsh Duty](#)

Catalogs

[Product Range Catalog Sensors – products, basic information, applications](#)

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - E58-30TD250-GLP-FC](#)

NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP69K



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia