

Eaton E58-30TS070-GAP

Catalog Number: E58-30TS070-GAP

Eaton harsh-duty sensor, E58 Tubular 30mm Photoelectric Sensor, Photoelectric, 1.18 dia., Forward Viewing, Sensor distance: 230 Ft., Stainless Steel encl, 4 Pin Pigtail Dual Key Micro Connector, 20-132 Vac 50/60 Hz or 15-30 Vdc input

General specifications



Product Name

Eaton harsh-duty sensor

Catalog Number

E58-30TS070-GAP

UPC

782114512074

Product Length/Depth

1.18 in

Product Height

4.36 in

Product Width

1.18 in

Product Weight

0.2688 lb

Warranty

3 year

Certifications

UL Listed

cUL Listed

CE



Powering Business Worldwide

defaultTaxonomyAttributeLabel

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Stainless steel

Operating mode

Thru-beam

Connection

4-pin pigtail dual key micro connector

Sensor type

Through beam

Switch type

Photoelectric

Input voltage

20-132 Vac at 50/60 Hz, 15-30 Vdc

LED indicator

Power on: red

Cord length

7 in

Operating temperature - max

131 °F

Operating temperature - min

-40 °F

Environmental rating

NEMA 1, NEMA 2, NEMA 3, NEMA 3R, NEMA 3S, NEMA 4,
NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP69K

Resources

Brochures

[Test the Best Photoelectric Sensors: E58 Series Harsh Duty](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

[Product Range Catalog Sensors – products, basic information, applications](#)

Specifications and datasheets

[Eaton Specification Sheet - E58-30TS070-GAP](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)